

HAKKO FX-301

SOLDERING POT

LEAD FREE



- Selectable heating programs allows to get optimum temperature quickly.
- Select from four heating programs: Sn-Pb (Tin/Lead), Sn-Ag-Cu (Tin/Silver/Copper), Sn-Cu (Tin/Copper), and Sn (Tin).
- Precise temperature control by digital temperature display & offset function.
- Use different pots for different composition solder, or different pot sizes (50 mm square and 75 mm square) with the same unit.
- A timer function helps you keep tabs on how long the soldering pot has been in use, making it easy to judge the time for pot replacement.

Easy Pot Replacement



Loosen the screws on both sides of the pot.



Replace the pot and retighten the screws.

Specifications

Model No.	FX-301
Power Consumption	200W
Weight (w/o solder & cord)	1.7kg
Dimensions	143 (W) x 100 (H) x 220 (D) mm

Soldering Pot

	50 x 50 Square	75 x 75 Square
Temperature Range	200-150 °C	200-380 °C
Dimensions	50 (W) x 43.5 (H) x 50 (D) mm	75 (W) x 52.5 (H) x 75 (D) mm
Molten Solder Capacity	0.85kg	1.2kg

*Only a 50 x 50 square solder pot is included in this product.
*The 75 x 75 square solder pot is an optional part.

Replacement Parts

Part No.	Name/Description
A1517	Solder pot/50 x 50mm
A1518	Solder pot/75 x 75mm

Temperature Probe

Part No.	Name/Description
A1310	Temperature probe/Total Length 1.2m for HAKKO 191, 192

Packing List

Model Name	Contents
HAKKO FX-301	Unit1
	Spatula1
	J-shaped waste collector1
	Hexagon wrench1

Dimensions of Solder Pot

